



LOS-961 ac

5GHz Line Of Sight (LOS) System

LOS-961 ac 5GHz is IP Based Digital Microwave that used in PTP and PTMP Mode. This Product delivers an extremely high 866Mbps throughput via its unique and powerful RF design that supports up to 256QAM modulation and 30dBm output power.

The LOS-961 ac 5GHz operating system ensures easy and rapid deployment of point-to-point links with stable, fast performance. An intuitive and responsive user interface adjusts the layout based on the size of your screen. Essential tools including Setup Wizard, link test, antenna alignment, spectrum analyzer, and site survey are included to make set-up and troubleshooting more efficient. Automatic mechanisms such as auto-channel and automatic transmit power control optimize the link for maximum performance even in areas with high interference.

Wireless										
Radio Mode	MIMO 2x2									
Radio Freq Band	4.9 – 6.1 GHz									
Transmit Power	30 dBm									
Receive Sensitivity	-75 ~ -97									
Channel Size	5, 10, 20, 40, 80 MHz									
Modulation	OFDM(256-QAM, 64-QAM, 16-QAM, QPSK, BPSK)									
Data Rate @ 80MHz	866, 780, 650, 585, 520, 390, 260, 195, 130, 65 Mbps									
Error Correction	BCC, LDPC									
Duplexing Scheme	TDD									
Modulation, Mbps	866	780	650	585	520	390	260	195	130	65
TX Power, dBm	24	25	25	26	27	28	28	29	29	30
Receive Sensitivity	-64	-66	-70	-72	-74	-78	-81	-85	-88	-90
Antenna										
Type	N-Type									
Gain	Antenna Dependent (Connectorized, Integrated 15,20 and 25 dBi)									
Software										
Wireless Operating Mode	Access Point, Station									
Wireless Techniques	Smart Auto-Channel, Auto Modulation, ATPC									
Wireless Security	WPA/WPA2(Personal and Enterprise involved), WACL, User isolation									
Wireless QoS	With Hardware acceleration									
WAN Protocols	Static IP, DHCP Client, PPPoE Client									
Service Watchdog	DHCP server, SNMP server, NTP client, Ping									
Management	HTTP(S) GUI, SSH, SNMP, WNMS, Telnet									
Tools	Site Survey, Link Test, Antenna Alignment									
Physical										
Dimensions	Length 198mm, Width 198mm, Height 46mm									
Weight	2.05 Kg									
Mounting	Pole Mounting									
Power										
Power Supply	100 ~ 240 VAC / 42 ~ 57 VDC POE 10/100/1000 Base-T, RJ45									
Power Consumption	10 W									
Environmental										
Temperature	-20°C ~ +55°C									
Humidity	0 ~ 90 %									